

风冷立式展示柜

Ventilated Vertical Showcase Series



主要结构特点

LC-246F LC-296F LC-350F

风机强制冷气循环, 快速制冷, 温度均匀;

The exhaust fan makes good air conditioning circulation, and rapid refrigeration and balanced temperature.

铝合金装饰门框, 中空防雾玻璃, 外观高档豪华;

The door frame decorated with aluminum alloy, with hollow antifogging glass door, features in looks top-grade and luxurious

箱顶设豪华广告灯箱, 内置立式照明灯管, 夜晚展示效果出众;

The ceiling has luxury advertising light boxes, built-in with vertical lighting pipe, fine display effect especial at night

设有上锁装置, 用户可自由选配门锁, 安全可靠;

It has lock equipment, and users can choose the lock at will. It is safe and reliable.

冷凝热风定向排放, 消除玻璃门凝露现象。

The heat air directional emission can prevent the glass door from congelation.

LC-800TM2F LC-1200TM2F

风机强制冷气循环, 快速制冷, 箱内温度均匀;

The exhaust fan makes good air conditioning circulation, and rapid refrigeration and balanced temperature.

中空防雾玻璃, 门体自动复位, 方便操作;

The hollow antifogging door will automatically return, convenient for operation.

内置立式照明灯管, 光照面积大, 夜晚展示效果更佳;

Built-in vertical lighting pipe with large lighting areas, fine display effect especial at night.

大容量、大面积展示, 适用于酒店、超市等商业场所。

Larger space to exhibit more goods, suitable for such business places as emporiums and supermarkets, etc.



东莞市百利电器有限公司
BAILI ELECTRIC CO., LTD.



百利

风冷立式冷藏展示柜



LC-246F
LC-296F
LC-350F

型号 Model	外型尺寸 Exterior Dimensions (L×D×H) (mm)	包装尺寸 Packing size (L×D×H) (mm)	有效容积 Available capacity (L)	输入功率 Input power (W)	冷藏温度 Refrigerating temperature (℃)	耗电量 Power consumption (kW.h/24h)	净重 Net weight (kg)	毛重 Cross weight (kg)	装箱数 40' GP
LC-246F	600×632×1699	683×724×1734	246	265	0~10	2.4	83	90	51
LC-296F	600×632×1874	683×724×1939	296	280	0~10	2.8	95	104	51
LC-350F	600×632×2080	683×724×2145	350	360	0~10	3.1	102	112	51

风冷双门立式冷藏展示柜



LC-800TM2F
LC-1200TM2F

型号 Model	外型尺寸 Exterior Dimensions (L×D×H) (mm)	包装尺寸 Packing size (L×D×H) (mm)	有效容积 Available capacity (L)	输入功率 Input power (W)	冷藏温度 Refrigerating temperature (℃)	耗电量 Power consumption (kW.h/24h)	净重 Net weight (kg)	毛重 Cross weight (kg)	装箱数 40' GP
LC-800TM2F	1012×703×2050	1080×775×2105	738	369	0~10	3.5	153	173	33
LC-1200TM2F	1362×703×2050	1430×775×2105	1025	433	0~10	4.0	195	225	24