



8 kg French fries/h

FD 50



12 kg French fries/h

FD 80 R



24 kg French fries/h

FD 80 DR

Ref.	Puissance Power	Dimensions hors tout Outside dimensions	Dimensions des paniers Basket dimensions	Volume Volume	Capacité (frites) Capacity (French fries)	Rendement (frites) Output (french fries)	Poids Weight	Volts Volts
FD 50	3,2 kW	215 x 425 x 320 mm	140 x 260 x 100 mm	5 L	1,5 kg	18 kg/h	5 kg	230 V
FD 80	3,4 kW	280 x 425 x 320 mm	220 x 260 x 100 mm	8 L	2,5 kg	12 kg/h	7 kg	230 V
FD 50 D	2 x 3,2 kW	390 x 425 x 320 mm	2 x (140 x 260 x 100 mm)	2 x 5 L	2 x 1,5 kg	16 kg/h	9 kg	2 x 230 V
FD 80 D	2 x 3,4 kW	540 x 425 x 320 mm	2 x (220 x 260 x 100 mm)	2 x 8 L	2 x 2,5 kg	24 kg/h	12 kg	2 x 230 V
FD 50 + 80	3,2 + 3,4 kW	490 x 425 x 320 mm	140 x 260 x 100 mm + 220 x 260 x 100 mm	5 + 8 L	1,5 + 2,5 kg	20 kg/h	13 kg	2 x 230 V
FD 80 R	3,4 kW	305 x 450 x 360 mm	220 x 260 x 100 mm	8 L	2,5 kg	12 kg/h	8 kg	230 V
FD 80 DR	2 x 3,4 kW	590 x 450 x 370 mm	2 x (220 x 260 x 100 mm)	2 x 8 L	2 x 2,5 kg	24 kg/h	15 kg	2 x 230 V

- Friteuses de table de **5 à 8 L à zone froide**.
- **Réarmement du thermostat de sécurité** derrière le boîtier.
- **Friteuses avec vidange FD 80 R / FD 80 DR** : cuve d'une seule pièce, emboutie et inclinée, spécialement conçue pour l'évacuation de l'huile sans manipulation de la friteuse. Vidange sécurisée grâce au robinet inox avec système de levier.
- **Friteuses à double cuve** 2 x 5 L et 2 x 8 L avec commandes indépendantes et caractéristiques identiques aux modèles 1 cuve.

**Entretien** : boîtier amovible et cuve inox lavable en machine.

**Équipement** : thermostat de régulation à bulbe précis 180°C, thermostat de sécurité, voyant de contrôle, panier avec poignée thermo-résistante, couvercle inox.

- **Table top fryers 5 to 8 L with cold zone**.
  - **Reset of safety thermostat** in the back in case of overheating or lack of oil.
  - **FD 80 R / FD 80 DR**: stamped and lightly tilted tank in one piece meant for easy oil draining. Safe draining with stainless-steel tap and lever system.
  - **Fryers with double tank** 2 x 5 L and 2 x 8 L with independent control and same specifications as single models.
- Cleaning**: removable control box and dishwasher-safe stainless-steel tank.
- Features**: precise bulb thermostat 180°C, safety thermostat, microswitch, pilot light, basket with heat-resistant handle, stainless steel lid.